

HARDi

LIGHTING

PCX Series

THERMOPLASTIC LED COMBO EMERGENCY EXIT UNIT

The PCX Series combines Energy Efficiency and Two Glare Free Emergency Mode Heads. Backplane Safety Pins that keep the unit safely mounted and True Bulb Downlight make this unit complete.

Construction

High Impact V5 Flame Retardant Thermoplastic

Finishes

Available in White or Black

Illumination

Provided by high output, low power consumption LEDs. Two Fully Adjustable 5.6 Watt Chrome Plated Heads. 1.8 Watts for Red / 2.5 Watts for Green

Installation

Complete Universal Mounting for Top, Side, Wall. Shipped complete with 2-Faceplates, 1-Back plate, and 1-Snap-On Canopy, Universal K/O's on back plate fit most standard size junction boxes.

Electrical

Field Selectable 120/277 Input Voltage Transformer. Automatic Low Voltage Disconnect (LVD) protects the battery from deep discharge. When normal AC power fails the solid state transfer switch automatically connects to the battery for 90 Minutes of power and is recharged in 24hours.

Features


- Super Bright Low Consumption LED's
- Damp Location Rated
- True Bulb Downlight
- Low Ceiling Mountable
- Universal Snap In/Out Chevrons

Warranty

Three Year Full Electronics Warranty.
Ten Year Battery Warranty.
(Five Years Full / Five Years Pro-rated)



Dimensions



Ordering Information

SERIES	PCX
LETTER COLOR	R-Red G-Green
CASE COLOR	W-White B-Black
FACE COLOR	W-White B-Black

Example: **PCX-G-WW**